



Session:

Date:

Time:

Chassis:

Track:

Temp:	Track	Outside
-------	-------	---------

Class:

Weather:	Sunny <input type="checkbox"/>
	Cloudy <input type="checkbox"/>
	Other <input type="checkbox"/>

Engine:

Gear:	Engine	Axle
-------	--------	------

Wheel Size / Offset	Wheel Spacing	Tire Compound	Tire Pressure	Tire Roll-out
Shock Valving	Shock Gas Pressure	Spring Rates	Bump Rubbers	Bump Packers
Ride Heights	Static Weights	Total Weight	Caster	Camber
		Cross %	Locked <input type="checkbox"/>	Ratchet <input type="checkbox"/>
		Left %		Free Wheel <input type="checkbox"/>
		Rear %		
		LR Bite		

Stagger:	Front	Rear	
Track Width:	Front	Rear	
Wheelbase:	Left	Right	
AXLE LEAD	FRONT	REAR	TOTAL

Front Panhard Position	Axle	Frame
Rear Panhard Position	Birdcage	Frame
Jacobs Ladder Position	Frame	Birdcage
LR Links	RR Links	

Notes:

Hot Box

Tire Pressures

Tire Roll-out

Stagger:

Front

Rear

Fastest Lap Times:	Total Number of Laps			
Lap	Time	RPM High	RPM Low	RPM Drops

BRIGGS GEAR CHART																
	AXLE															
	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	
26	5.14	5.37	5.60	5.84	6.07	6.30	6.54	6.77	7.00	7.24	7.47	7.70	7.94	8.17	8.40	
27	4.95	5.17	5.40	5.62	5.85	6.07	6.29	6.52	6.74	6.97	7.19	7.42	7.64	7.87	8.09	
28	4.77	4.99	5.20	5.42	5.64	5.85	6.07	6.29	6.50	6.72	6.94	7.15	7.37	7.59	7.80	
29	4.60	4.81	5.02	5.23	5.44	5.65	5.86	6.07	6.28	6.49	6.70	6.91	7.12	7.33	7.54	
30	4.45	4.65	4.86	5.06	5.26	5.46	5.67	5.87	6.07	6.27	6.47	6.68	6.88	7.08	7.28	
31	4.31	4.50	4.70	4.90	5.09	5.29	5.48	5.68	5.87	6.07	6.27	6.46	6.66	6.85	7.05	
32	4.17	4.36	4.55	4.74	4.93	5.12	5.31	5.50	5.69	5.88	6.07	6.26	6.45	6.64	6.83	
33	4.05	4.23	4.41	4.60	4.78	4.97	5.15	5.33	5.52	5.70	5.89	6.07	6.25	6.44	6.62	
34	3.93	4.11	4.28	4.46	4.64	4.82	5.00	5.18	5.36	5.53	5.71	5.89	6.07	6.25	6.43	
35	3.82	3.99	4.16	4.34	4.51	4.68	4.86	5.03	5.20	5.38	5.55	5.72	5.90	6.07	6.24	
36	3.71	3.88	4.05	4.22	4.38	4.55	4.72	4.89	5.06	5.23	5.40	5.56	5.73	5.90	6.07	
37	3.61	3.77	3.94	4.10	4.27	4.43	4.59	4.76	4.92	5.09	5.25	5.41	5.58	5.74	5.91	
38	3.51	3.67	3.83	3.99	4.15	4.31	4.47	4.63	4.79	4.95	5.11	5.27	5.43	5.59	5.75	
39	3.42	3.58	3.74	3.89	4.05	4.20	4.36	4.51	4.67	4.82	4.98	5.14	5.29	5.45	5.60	
40	3.34	3.49	3.64	3.79	3.95	4.10	4.25	4.40	4.55	4.70	4.86	5.01	5.16	5.31	5.46	
41	3.26	3.41	3.55	3.70	3.85	4.00	4.15	4.29	4.44	4.59	4.74	4.89	5.03	5.18	5.33	
42	3.18	3.32	3.47	3.61	3.76	3.90	4.05	4.19	4.34	4.48	4.62	4.77	4.91	5.06	5.20	

HONDA GEAR CHART																
	AXLE															
	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	
26	5.20	5.43	5.67	5.90	6.14	6.38	6.61	6.85	7.08	7.32	7.56	7.79	8.03	8.27	8.50	
27	5.00	5.23	5.46	5.69	5.91	6.14	6.37	6.59	6.82	7.05	7.28	7.50	7.73	7.96	8.19	
28	4.82	5.04	5.26	5.48	5.70	5.92	6.14	6.36	6.58	6.80	7.02	7.24	7.46	7.68	7.89	
29	4.66	4.87	5.08	5.29	5.50	5.72	5.93	6.14	6.35	6.56	6.78	6.99	7.20	7.41	7.62	
30	4.50	4.71	4.91	5.12	5.32	5.53	5.73	5.94	6.14	6.34	6.55	6.75	6.96	7.16	7.37	
31	4.36	4.56	4.75	4.95	5.15	5.35	5.55	5.74	5.94	6.14	6.34	6.54	6.73	6.93	7.13	
32	4.22	4.41	4.61	4.80	4.99	5.18	5.37	5.56	5.76	5.95	6.14	6.33	6.52	6.72	6.91	
33	4.09	4.28	4.47	4.65	4.84	5.02	5.21	5.40	5.58	5.77	5.95	6.14	6.33	6.51	6.70	
34	3.97	4.15	4.33	4.51	4.70	4.88	5.06	5.24	5.42	5.60	5.78	5.96	6.14	6.32	6.50	
35	3.86	4.03	4.21	4.39	4.56	4.74	4.91	5.09	5.26	5.44	5.61	5.79	5.96	6.14	6.32	
36	3.75	3.92	4.09	4.26	4.43	4.61	4.78	4.95	5.12	5.29	5.46	5.63	5.80	5.97	6.14	
37	3.65	3.82	3.98	4.15	4.31	4.48	4.65	4.81	4.98	5.14	5.31	5.48	5.64	5.81	5.97	
38	3.55	3.72	3.88	4.04	4.20	4.36	4.52	4.69	4.85	5.01	5.17	5.33	5.49	5.66	5.82	
39	3.46	3.62	3.78	3.94	4.09	4.25	4.41	4.57	4.72	4.88	5.04	5.20	5.35	5.51	5.67	
40	3.38	3.53	3.68	3.84	3.99	4.14	4.30	4.45	4.61	4.76	4.91	5.07	5.22	5.37	5.53	
41	3.29	3.44	3.59	3.74	3.89	4.04	4.19	4.34	4.49	4.64	4.79	4.94	5.09	5.24	5.39	
42	3.22	3.36	3.51	3.65	3.80	3.95	4.09	4.24	4.39	4.53	4.68	4.82	4.97	5.12	5.26	